

## Granville Running In Oil

5 Litre

### PRODUCT DESCRIPTION

Running In Oil is low detergent, non friction modified oil specially formulated to promote the bedding in of newly machined mated surfaces in re-built engines. High quality additives overcome bore glazing allowing accurate seating of the piston rings and valves. Can be used for up to 1000 miles of normal road use.

### PRODUCT BENEFITS

- \* Non detergent oil
- \* Ensures correct bedding in of newly machined mated surfaces
- \* Eliminates bore glaze

### PRODUCT USAGE

For limited use in newly re-built petrol and diesel engines which can be used for up to 1000 miles of normal road use. Ideal for use in engine on test benches.

### STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children.

### SHELF LIFE

5 years from date of manufacture

- Appearance** : Amber liquid
- Odour** : Characteristic
- Solubility** : Insoluble in water



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
5 Litre	1821	5020618018216



# Granville Running In Oil

5 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	10.57
HTHS Viscosity	ASTM D4683	mPa.s	2.9		
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			89.87
Density	ASTM D792	@ 15°C			0.876
Total Base Number	ASTM D2896	mg KOH/g			6.22
Viscosity Index	ASTM D2270		75		
Pour Point	ASTM D97	°C		-15	

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

